

TEST CERTIFICATE

BS 5609: 2024 (Section Two)



Client: Premier Coating and Converters Ltd

Product reference: PL0117

Facestock: 175µm Matt White Polyolefin

Adhesive code: PCC17

Smithers Ref: 24-1005014 Y1

Tests passed	Standard reference
Adhesion after marine immersion – Aluminium and HDPE	4.2
Dimensional stability	4.3.1
Adhesion after 48 hours - Aluminium	4.3.2
Adhesion after artificial weathering - Aluminium	4.3.3
Adhesion after temperature cycle - Aluminium	4.3.4
Colourfastness	4.3.5
Adhesion after 48 hours - HDPE	4.4.1
Adhesion after temperature cycle - HDPE	4.4.2

This is to certify that the above label base material has been tested by Smithers and conforms to BS 5609: 2024 Section 2 – Pressure-sensitive, adhesive-coated facestock.



Signed: pp.....

Dave Stone

Dated: 24th February 2026

Version Number	Date	Description	Reason for changes	Author or Originator
01	23 rd October 2015	Original Document. BS 5609: 1986 Reference 15-131127	N/A	Maggie Carnegie
02	5 th November 2021	Update	Updated Product Reference	Dave Stone
03	24 th February 2026	Updated to BS 5609: 2024	Passed the additional tests on HDPE	Dave Stone

Any measurement has some uncertainty, which is mainly due to the accuracy and precision of the method and equipment used to make the measurement. This needs to be taken into account for UKAS accredited (ISO 17025) testing when results are reported against a specification. The uncertainty of measurement is assessed and this is used to calculate the probability of false acceptance (passing a result that should fail) or false rejection (failing a result that should pass).

In order to qualify as a Pass there must be a 5% or less chance of a false positive. Where the recorded result is within specification, but there is a more than 5% chance that it could have been out of specification, a "Conditional Pass" is reported. This 'non-binary acceptance' approach is defined in ILAC G8:09/2019 Guidelines on Decision Rules and Statements of Conformity.